



RESISTANCE READINGS

| ITEM | TUBE | Pin 1 | Pin 2 | Pin 3 | Pin 4 | Pin 5 | Pin 6 | Pin 7 | Pin 8 |
|------|------|-------|--------|--------|--------|--------|-------|-------|-------|
| V1 | 65C7 | 0Ω | 1.250K | 100Meg | 1.250K | 0Ω | 200Ω | 200Ω | 200Ω |
| V2 | 65C7 | 0Ω | 1.210K | 0Ω | 1.210K | 1800Ω | 200Ω | 200Ω | 200Ω |
| V3 | 65C7 | 0Ω | 1.400K | 10K | 500K | 1.400K | 1500Ω | 200Ω | 200Ω |
| V4 | 6L6G | 0Ω | 200Ω | 1.107Ω | 1.750Ω | 480K | NC | 200Ω | 200Ω |
| V5 | 6L6G | 0Ω | 200Ω | 1.100Ω | 1.750Ω | 470K | NC | 200Ω | 200Ω |
| V6 | 5U4G | NC | 50K | NC | 75Ω | TP | 65Ω | NC | 50K |

RESISTANCE READINGS TAKEN FROM PIN 6 OF V6.
 NC = NO CONNECTION
 TP = TIE POINT

- DC voltage measurements taken with vacuum tube voltmeter.
- AC voltages measured at 1000 ohms per volt.
- Socket connections are shown as bottom views.
- Measured values are given in ohms unless otherwise specified.
- Use appropriate tolerance for voltage resistors.
- Nominal tolerance of component values makes possible a variation of ±1% in voltage and resistance readings.
- All controls at minimum, proper output load connected.

SEE PARTS LIST FOR ALTERNATE VALUE OR APPLICATION

A PHOTOFACT STANDARD NOTATION SCHEMATIC
 © Howard W. Sams & Co., Inc. 1957