


NOTES

- ALL RESISTORS IN OHMS 1/2W 10% UNLESS OTHERWISE SPECIFIED
- ALL CAPACITORS IN MFD AND 400V 10% UNLESS OTHERWISE SPECIFIED.
- D.C. VOLTAGE READINGS WITH NO SIGNAL APPLIED USING A 20,000 Ω PER VOLT VOLTMETER.
- NUMBERS IN PARENTHESIS REFER TO AMPEG S PART NO.
- * 2A FUSE SHOULD BE IN 240V MODELS ONLY
- D.C. VOLTAGE READINGS ARE POSITIVE WITH RESPECT TO GROUND UNLESS OTHERWISE SPECIFIED
- CIRCUIT OF CHASSIS MAY VARY SLIGHTLY FROM THAT SHOWN HERE DUE TO NORMAL PRODUCTION CHANGES
- ** RES. 60, 61, 62, 63 & 64 ARE LOCATED ON SW1.
- * - THE P.T. FOR 240V MODELS HAS BLK WIRE CONNECTED TO BLUE WH AS DOTTED LINE SHOWS



AREA CODE 1201 732 4300
ampeg
LINDEN, NEW JERSEY 07036

MODEL
B155
U.S. PATENT PENDING

DRN BY	DATE	DWG. NO	PART NO	REV.
S.C.	3-71	06400	40102580	C