


SPECIFICATIONS

LARGE ROUND



LOUDSPEAKERS

Model	8 H	FERRITE C8L	8 M
Power handling capacity	6 Watts Peak	6 Watts Peak	10 Watts Peak
Diaphragm	F74	F74	F59
Fundamental resonance	110 c.p.s.	110 c.p.s.	75 c.p.s.
Frequency response	105 c.p.s. — 7 K.C.	105 c.p.s. — 7 K.C.	70 c.p.s. — 8 K.C.
Voice coil impedance	3.5 or 15 ohms at 400 c.p.s.	15 ohms at 400 c.p.s.	2 or 15 ohms at 400 c.p.s.
Air gap flux density	9,200 Gauss	10,600 Gauss	9,350 Gauss
Gap flux	23,000 Lines	31,800 Lines	36,200 Lines
Transformer	Type Q or D	Type Q or D	Type K or C
Principal dimensions:			
Overall diameter of diaphragm housing	8 $\frac{1}{16}$ "	8 $\frac{1}{16}$ "	8 $\frac{1}{16}$ "
Diameter of baffle opening	7 $\frac{1}{16}$ "	7 $\frac{1}{16}$ "	7 $\frac{1}{16}$ "
Diameter of voice coil	3/4"	3/4"	1"
Depth from pad ring to rear	3 $\frac{1}{16}$ "	2 $\frac{1}{16}$ "	3 $\frac{3}{16}$ "
Mounting	Four 5/16" x 7/32" slots spaced 90° on 7 $\frac{19}{32}$ " pitch circle diameter	Four 5/16" x 7/32" slots spaced 90° on 7 $\frac{19}{32}$ " pitch circle diameter	Four 5/16" x 7/32" slots spaced 90° on 7 $\frac{19}{32}$ " pitch circle diameter
Finish	Baked enamel housing, magnet assembly black lacquered	Baked enamel housing	Baked enamel housing, magnet assembly black lacquered
Weight (without transformer)	1 lb. 1/4 oz.	1 lb. 1 $\frac{1}{2}$ ozs.	1 lb. 7 $\frac{3}{4}$ ozs.

SPECIAL ELECTRIC GUITAR MODELS

Model	12 M	12 PEG	12 UEG
Power handling capacity	10 Watts Peak	20 Watts Peak	30 Watts Peak
Diaphragm	F27	F36	F20
Fundamental resonance	85 c.p.s.	40 c.p.s.	40 c.p.s.
Frequency response	80 c.p.s. — 6.5 K.C.	35 c.p.s. — 5.5 K.C.	35 c.p.s. — 5.5 K.C.
Voice coil impedance	2 or 15 ohms at 400 c.p.s.	15 ohms at 400 c.p.s.	8 or 15 ohms at 400 c.p.s.
Air gap flux density	9,350 Gauss	12,800 Gauss	14,000 Gauss
Gap flux	36,200 Lines	87,000 Lines	150,000 Lines
Transformer	Type K or C	Not supplied	Not supplied
Principal dimensions:			
Overall diameter of diaphragm housing	12 $\frac{3}{32}$ "	12 $\frac{3}{32}$ "	12 $\frac{3}{32}$ "
Diameter of baffle opening	10 $\frac{29}{32}$ "	10 $\frac{29}{32}$ "	10 $\frac{29}{32}$ "
Diameter of voice coil	1"	1 $\frac{3}{4}$ "	1 $\frac{3}{4}$ "
Depth from pad ring to rear	4 $\frac{1}{16}$ "	4 $\frac{3}{4}$ "	7"
Mounting	Four 1/4" holes spaced 90° on 11 $\frac{9}{8}$ " pitch circle diameter	Four 1/4" holes spaced 90° on 11 $\frac{5}{8}$ " pitch circle diameter	Four 3/8" x 1/4" slots spaced 90° on 11 $\frac{5}{8}$ " pitch circle diameter
Finish	Baked enamel housing, magnet assembly black lacquered	Baked enamel housing, magnet assembly black lacquered	Baked enamel housing, magnet assembly black lacquered
Weight (without transformer)	2 lb. 5 ozs.	3 lb. 7 $\frac{1}{2}$ ozs.	7 lb. 10 $\frac{3}{4}$ ozs.