



RESISTANCE READINGS

Item	Tuben	Pin 1	Pin 2	Pin 3	Pin 4	Pin 5	Pin 6	Pin 7	Pin 8
V 1	6SC7	0Ω	132KΩ	6MΩ	132KΩ	0Ω	220Ω	220Ω	220Ω
V 2	6SJ7	0Ω	220Ω	100KΩ	1KΩ	1200KΩ	220Ω	1100KΩ	1100KΩ
V 3	6SJ7	0Ω	220Ω	180KΩ	35KΩ	2.2KΩ	180KΩ	220Ω	180KΩ
V 4	6SN7GT	18KΩ	130KΩ	1KΩ	470KΩ	130KΩ	1KΩ	220Ω	220Ω
V 5	6L6G	0Ω	220Ω	110Ω	12500Ω	270KΩ	130KΩ	220Ω	200Ω
V 6	6L6G	0Ω	220Ω	120Ω	12500Ω	270KΩ	130KΩ	220Ω	200Ω
V 7	5U4G	Infl.	20KΩ	Infl.	50Ω	20KΩ	42Ω	Infl.	20KΩ

† MEASURED FROM PIN 8 OF V1

THE COOPERATION OF THE MANUFACTURER OF THIS EQUIPMENT MAKES IT POSSIBLE TO BRING YOU THIS SERVICE

A PHOTOFACT STANDARD NOTATION SCHEMATIC  
© Howard W. Sams & Co., Inc. 1951

1. DC voltages measurements are at 20,000 ohms per volt; AC voltages measured at 1000 ohms per volt.
2. Socket connections are shown as bottom views.
3. Measured values are from socket pin to common negative.
4. Line voltage maintained at 117 volts for voltage readings.
5. Nominal tolerance on component values makes possible a variation of ± 15% in voltage and resistance measurements.
6. All controls at minimum, proper output load connected.