

# THE DWAMP

		Measured	Calculated		
		Line		232 V AC	
		Heaters		6,7 V AC	
		Heaters V8		6,6 V AC	
V8	EZ80	Pin 1 Anode		305 V AC	
		Pin 7 Anode		313 V AC	
		Pin 3 Cathode		326 V DC	
		100mA Choke	I Choke	108 Ohm	101,9 mA
		Voltage across choke		10,25 V AC	94,9 mA
HT		B+1 OT V5		315 V DC	
		R B+2	I (R B+2)	327,4 Ohm	42,8 mA
		B+2 B+3 - B+8		301 V DC	
		R B+3	I (R B+3)	999 Ohm	25,0 mA
		B+3 OT V6		276 V DC	
		R B+4	I (R B+4)	9990 Ohm	4,5 mA
		B+4 G2 V5		256 V DC	
		R B+5	I (R B+5)	666 Ohm	13,5 mA
		B+5 V3, V4 & B+6		292 V DC	
		R B+6	I (R B+6)	6720 Ohm	2,4 mA
		B+6 V7		276 V DC	
		R B+7	I (R B+7)	9960 Ohm	6,1 mA
		B+7 V1 & V2		240 V DC	
		B+8 Heater Elevation		45 V DC	
		B+9 2 <sup>nd</sup> HT winding		231 V DC	
V5	6V6	Pin 3 Anode	Anode Voltage	283 V DC	273,0 V DC
		R G2	Screen Current	1000 Ohm	2,0 mA
		Pin 4 G2	Screen Voltage	254 V DC	244,0 VDC
		Pin 5 G1		0 V DC	
		R C		199,3 Ohm	
		Pin 8 Cathode	Cathode Current	10 V DC	50,2 mA
			Anode Current		48,2 mA
			Plate Dissipation	13,2 W	94%
V6	EL95	Pin 5 Anode	Anode Voltage	267 V DC	257,8 V DC
		R G2	Screen Current	465 Ohm	4,3 mA
		Pin 6 Screen	Screen Voltage	229 V DC	219,8 V DC
		Pin 1 G1		0 V DC	
		RC		325 Ohm	
		Pin 2 Cathode, G3	Cathode Current	9,2 V DC	28,3 mA
			Anode Current		24,0 mA
			Plate Dissipation	6,2 W	103%

21.01.2020

# THE DWAMP

V7	EF86	Pin 1	G2	113,0 V DC
		Pin 3	Cathode	1,7 V DC
		Pin 6	Anode	127,0 V DC
		Pin 8	G3	1,7 V DC
		Pin 9	G1	0,0 V DC
V4	6N2P	Pin 1	Anode	148 V DC
		Pin 2	Grid	0 V DC
		Pin 3	Cathode	1,7 V DC
		Pin 6	Anode	170 V DC
		Pin 7	Grid	0 V DC
V3	12AU7	Pin 1	Anode	59 V DC
		Pin 2	Grid	0 V DC
		Pin 3	Cathode	2,3 V DC
		Pin 6	Anode	291 V DC
		Pin 7	Grid	68 V DC
V2	6N2P	Pin 8	Cathode	123 V DC
		Pin 1	Anode	240 V DC
		Pin 2	Grid	134 V DC
		Pin 3	Cathode	134 V DC
		Pin 6	Anode	96 V DC
V1	6N2P	Pin 7	Grid	0 V DC
		Pin 8	Cathode	0,8 V DC
		Pin 1	Anode	148 V DC
		Pin 2	Grid	0 V DC
		Pin 3	Cathode	1,4 V DC
		Pin 6	Anode	111 V DC
		Pin 7	Grid	0 V DC
		Pin 8	Cathode	1,4 V DC