



TO PIN 11 ON C.B. SUB-CHASSIS
 TO PIN 1 ON TUBE SOCKET
 FOR LOWEST C ON
 C.B. SUB-CHASSIS.

GREEN → X
 GREEN → X
 YELLOW 17V
 RED 170V
 ORANGE
 BLACK

SELECTED RESISTORS

B ½ W - IN THE RANGE 5.6K TO 56 K (SINGLE ± 10% ½ W RESISTOR)
 C 1 W - FROM THE VALUES 39K, 47K, 68K (SINGLE RESISTOR DOWN TO
 39K SHUNT : 2, 3, 4 RESISTORS FOR)

F SELECTED FROM MEASURED VALUES OF
 G SELECTED FROM MEASURED VALUES OF
 H SELECTED FROM MEASURED VALUES OF
 I SELECTED FROM MEASURED VALUES OF
 J SELECTED FROM MEASURED VALUES OF
 K SELECTED FROM MEASURED VALUES OF
 L SELECTED FROM MEASURED VALUES OF
 M SELECTED FROM MEASURED VALUES OF
 N SELECTED FROM MEASURED VALUES OF
 O SELECTED FROM MEASURED VALUES OF
 P SELECTED FROM MEASURED VALUES OF
 Q SELECTED FROM MEASURED VALUES OF
 R SELECTED FROM MEASURED VALUES OF
 S SELECTED FROM MEASURED VALUES OF
 T SELECTED FROM MEASURED VALUES OF
 U SELECTED FROM MEASURED VALUES OF
 V SELECTED FROM MEASURED VALUES OF
 W SELECTED FROM MEASURED VALUES OF
 X SELECTED FROM MEASURED VALUES OF
 Y SELECTED FROM MEASURED VALUES OF
 Z SELECTED FROM MEASURED VALUES OF

NOTE #2

NOTE #1