



- ⚠ USED IN SOME VERSIONS.
 - ⚠ MASTER VOLUME PUSH-PULL SWITCH DESIGNATED "MVS" SHOWN IN "OUT" POSITION, PUSH IN FOR PURE SOUND.
 - ⓂV DENOTE TYPICAL 1KHZ SIGNAL REQUIRED FOR 10 WATT OUTPUT AND [500MV] REVERB INPUT COIL DRIVE.
4. SIX DIGIT NUMBERS ARE FENDER PART NUMBERS.
 3. ALL CAPACITORS AT LEAST 600V, W.V.D.C.
 2. ALL RESISTORS 1/2 WATT ±10%.
 1. VOLTAGES READ TO GROUND WITH V.T.V.M. NO SIGNAL. V5 (ONLY) VOLTAGES READ WITH SPEED & INTENSITY MAX. & VIBRATO ON.

CAUTION:
 500 VOLTS AVAILABLE - DISCONNECT POWER SUPPLY AND ALLOW AT LEAST 30 SECONDS FOR VOLTAGES TO "BLEED" OFF, BEFORE SERVICING AMPLIFIER.

DWN	RON RICO	2/24/77
CHK		3/24/77
APP		
REP		1/11/77

Fender/Rogers/Rhodes
 ONE HUNDRED NINETEEN & A DIVISION OF GEL, INC.
 FULLERTON, CALIFORNIA 92631

PART NAME
SCHEMATIC
135 WATT RMS AMP
W/REVERB AND VIBRATO

RELEASE DATE: 1964
 SIZE: D
 PART NO.: 013694
 REV: D

NOTES: UNLESS OTHERWISE SPECIFIED